


TERMINALES BIMETÁLICOS, SOLDADOS A FRICCIÓN, ENGASTADO HEXAGONAL



Bimetallic friction welded lugs for hexagonal pressing
Cosses bimétalliques, soudées à froid, sertissage hexagonal



Material:
E-Cu
Al 99,5



PIEZAS DE DIMENSIONAMIENTO CENTRO EUROPEO
Central Europe Dimensions

CABLE SIZE mm ²		TORNILLO Hole for M	L	A	Ø D	L1	NÚMERO DE APRIETES Number of crimps		MATRIZ Die size	REF.
rm sm	se						TENAZA Handtool	Hydraulic		
25		8	65	20	6,8	37	4	2	12	GBL 25-8
		10		25						25-10
		12		26						25-12
35		10	75	20	8	47	5	3	14	GBL 35-10
		12		26						35-12
50		10	75	20	9,8	47	5	3	16	GBL 50-10
		12		26						50-12
70		10	85	26	11,2	55	6	3	18	GBL 70-10
		12								70-12
95		12	85	26	13,2	57	6	3	22	GBL 95-10
		16		30						95-16
120		12	87	26	14,7	57	6	3	22	GBL 120-12
		16		30						120-16
150		12	100		16,3	67		3	25	GBL 150-12
		16		30						150-16
		20								150-20
185		12	101	30	18,3	68		3	28	GBL 185-12
		16		36						185-16
240		12	112	30	21	79		3	32	GBL 240-12
		16		36						240-16
300		16	120	42	23,3	79		3	34	GBL 300-16
		20		42						300-20